

New

SIGNODE[®]

Table-Tyer SS

▲ Stainless Steel Frame

▲ Side Seal

▲ Durable

▲ Reliable

Designed for the Marine Food Industry

- ▲ Sturdy
- ▲ Compact
- ▲ Economical
- ▲ Smooth, Quiet Operation

Advantages

Quiet 24V DC drive motors run only when machine is cycling

No chains, belts, or pulleys

Electronic tension
17 - 100 lbs

Adjustable roller table height
15-1/2" - 27"

All DC motors & heater are "stepped down" to 24V to increase machine safety

Signode's one year warranty on all parts, available through your local Signode Distributor



Easy Operation Panel

Special features of the Signode® Table-Tyer SS

- ▲ Unique frame design is exceptionally sturdy and durable
- ▲ Elimination of chain, belts, and pulley and the simplistic design substantially reduces maintenance issues
- ▲ Roller table height is adjustable to any height between 15-1/2" - 27"
- ▲ Adjustable tension and strap feed for efficient use
- ▲ All DC motors and heater are "stepped down" to 24V to prolong the life of the heat knife and to increase safety
- ▲ Quiet 24V DC drive motors run only when machine is cycling
- ▲ Wide electronic control tension range from 17 - 100 lbs
- ▲ Uses low cost Signode SDM™ polypropylene strapping
- ▲ Sealing head is adjustable to any strap size from 1/4" - 1/2" (6 mm - 12 mm)
- ▲ Fast heating sealing mechanism is sensor controlled, assuring you of a long life of consistent, high-efficiency seals
- ▲ Adjustable weld cool time for consistent, high-efficiency seals, even under high tension
- ▲ Signode's one year warranty on all parts through your local Signode Distributor

Machine Specifications

Maximum package weight:
125 lbs

Tension:
17 - 100 lbs

Strapping:
Signode SDM™ plastic strapping
(Accepts 8" or 9" core)

Weight: 168 lbs

Power Supply: 120V, 60Hz, 1Ph

SDM Strap Specifications

| Strap Type | Width | Average Break Strength | Feet per Coil |
|------------|---------------|-------------------------------|---------------------|
| SDM 14-180 | 1/4" (0.236") | 6 mm 180 lbs (890 N) | 20,000 (5 486 m) |
| SDM 38-300 | 3/8" (0.350") | 9 mm 300 lbs (1 334 N) | 12,900 (3 932 m) |
| SDM 12-300 | 1/2" (0.470") | 12 mm 300 lbs (1 557 N) | 9,900 (3 018 m) |
| SDM 12-500 | 1/2" (0.470") | 12 mm 500 lbs (1 557 N) | 6,600 (3 018 m) |

Distributed by:

 **SIGNODE®**

Signode Distributor Sales
180 Hastings Drive
Buffalo Grove, IL 60089
1-800-526-1948
Fax 1-847-215-9599